

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

TABLE OF CONTENTS—ALPHABETICAL

Subject	Standard	Page
ABC-NACO Technologies (formerly National Castings)—Designs	S-393	S-II[S-393]345
Amsted Rail (Formerly ABC-NACO)—Design Details	S-392	S-II[S-392]61
Amsted Rail (Formerly Buckeye)—Design Details	S-392	S-II[S-392]181
Amsted Rail (Formerly Pennsy)—Design Details	S-392	S-II[S-392]171
Amsted Rail—Design Details	S-392	S-II[S-392]121
ASF-Keystone, Inc.—Designs	S-393	S-II[S-393]363
Birdsboro Corporation—Designs	S-393	S-II[S-393]389
Bolster—Tolerances	S-316	S-II[S-316]19
Bolster, 14 in. Center Plate—Limiting Outline	S-310	S-II[S-310]11
Bolster, 16 in. Center Plate—Limiting Outline	S-311	S-II[S-311]13
Bolster, Truck—Marking Diagram	S-312	S-II[S-312]15
Buckeye Steel Castings—Designs	S-393	S-II[S-393]395
Canadian Steel Foundries—Designs (by American Steel Foundries, now ASF-Keystone, Inc.)	S-393	S-II[S-393]437
Canadian Steel Foundries—Designs (by National Castings, now ABC-NACO Technologies)	S-393	S-II[S-393]435
Dofasco—Designs	S-393	S-II[S-393]441
Dofasco—Designs (by National Castings, now ABC-NACO Technologies)	S-393	S-II[S-393]445
Dresser Transportation Equipment Division—Designs	S-393	S-II[S-393]447
Fundiciones de Hierro y Acero, S.A.—Designs (ceased production in 1992)	S-393	S-II[S-393]463
Ohio Steel Foundry—Designs	S-393	S-II[S-393]465
Pittron—Designs	S-393	S-II[S-393]467
Scullin Steel Company—Designs	S-393	S-II[S-393]475
Side Frame—Bolster Rotation Stop Lug	S-318	S-II[S-318]23
Side Frame—Roof Repair	S-327	S-II[S-327]29
Side Frame—Tolerances	S-317	S-II[S-317]21
Side Frame—Wide Land Rotation Stop Lug Column	S-319	S-II[S-319]25
Side Frame, Alternate Standard Pedestal-Type with Side Frame Key—Application of Roller Bearing Unit	S-3012	S-II[S-3012]495
Side Frame, Narrow Pedestal—Limiting Dimensions	S-325	S-II[S-325]27
Side Frame, Narrow Pedestal—Roller Bearing	S-329	S-II[S-329]33
Side Frame, Standard Pedestal-Type with Side Frame Key—Limiting Dimensions	S-3010	S-II[S-3010]491
Side Frame, Truck—Marking Diagram	S-314	S-II[S-314]17
Side Frames and Bolsters—Produced Prior to 1978	S-393	S-II[S-393]339
Side Frame, Cast Steel—Marking and Mating	S-378	S-II[S-378]37
Side Frame, Standard Pedestal-Type Size 6 in. × 11 in. with Side Frame Key—Limiting Dimensions	S-3011	S-II[S-3011]493

IMPLEMENTED 02/15/2019

AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes

Subject	Standard	Page
Siderurgica Nacional, S.A.—Designs (Sahagun, Mexico; now owned jointly by National Castings de Mexico, S.A. de C.V. and ABC-NACO Technologies)	S-393	S-II[S-393]489
Standard Car Truck Company—Drawings	S-392	S-II[S-392]207
Truck—Design Drawings	S-392	S-II[S-392]39
Truck, 33-in. Wheels—Design Dimensions	S-301	S-II[S-301]5
Truck, 36 in. Wheels—Design Dimensions	S-302	S-II[S-302]7
Truck, 38 in. Wheels—Design Dimensions	S-304	S-II[S-304]9
Truck, Freight Car—Design Data	S-300	S-II[S-300]1
Unit Guide Bracket, EC-2055—Design Dimensions	S-366	S-II[S-366]35

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

TABLE OF CONTENTS—NUMERICAL

Standard	Subject	Page
S-300	Truck, Freight Car—Design Data	S-II[S-300]1
S-301	Truck, 33-in. Wheels—Design Dimensions	S-II[S-301]5
S-302	Truck, 36 in. Wheels—Design Dimensions	S-II[S-302]7
S-304	Truck, 38 in. Wheels—Design Dimensions	S-II[S-304]9
S-310	Bolster, 14 in. Center Plate—Limiting Outline	S-II[S-310]11
S-311	Bolster, 16 in. Center Plate—Limiting Outline	S-II[S-311]13
S-312	Bolster, Truck—Marking Diagram	S-II[S-312]15
S-314	Side Frame, Truck—Marking Diagram	S-II[S-314]17
S-316	Bolster—Tolerances	S-II[S-316]19
S-317	Side Frame—Tolerances	S-II[S-317]21
S-318	Side Frame—Bolster Rotation Stop Lug	S-II[S-318]23
S-319	Side Frame—Wide Land Rotation Stop Lug Column	S-II[S-319]25
S-325	Side Frame, Narrow Pedestal—Limiting Dimensions	S-II[S-325]27
S-327	Side Frame—Roof Repair	S-II[S-327]29
S-329	Side Frame, Narrow Pedestal—Roller Bearing	S-II[S-329]33
S-366	Unit Guide Bracket, EC-2055—Design Dimensions	S-II[S-366]35
S-378	Side Frame, Cast Steel—Marking and Mating	S-II[S-378]37
S-392	Truck—Design Drawings	S-II[S-392]39
S-392	Amsted Rail (Formerly ABC-NACO)—Design Details	S-II[S-392]61
S-392	Amsted Rail—Design Details	S-II[S-392]121
S-392	Amsted Rail (Formerly Pennsy)—Design Details	S-II[S-392]171
S-392	Amsted Rail (Formerly Buckeye)—Design Details	S-II[S-392]181
S-392	Standard Car Truck Company—Drawings	S-II[S-392]207
S-393	Side Frames and Bolsters—Produced Prior to 1978	S-II[S-393]339
S-393	ABC-NACO Technologies (formerly National Castings)—Designs	S-II[S-393]345
S-393	ASF-Keystone, Inc.—Designs	S-II[S-393]363
S-393	Birdsboro Corporation—Designs	S-II[S-393]389
S-393	Buckeye Steel Castings—Designs	S-II[S-393]395
S-393	Canadian Steel Foundries—Designs (by National Castings, now ABC-NACO Technologies)	S-II[S-393]435
S-393	Canadian Steel Foundries—Designs (by American Steel Foundries, now ASF-Keystone, Inc.)	S-II[S-393]437
S-393	Dofasco—Designs	S-II[S-393]441
S-393	Dofasco—Designs (by National Castings, now ABC-NACO Technologies)	S-II[S-393]445
S-393	Dresser Transportation Equipment Division—Designs	S-II[S-393]447
S-393	Fundiciones de Hierro y Acero, S.A.—Designs (ceased production in 1992)	S-II[S-393]463
S-393	Ohio Steel Foundry—Designs	S-II[S-393]465
S-393	Pittron—Designs	S-II[S-393]467
S-393	Scullin Steel Company—Designs	S-II[S-393]475

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

Standard	Subject	Page
S-393	Siderurgica Nacional, S.A.—Designs (Sahagun, Mexico; now owned jointly by National Castings de Mexico, S.A. de C.V. and ABC-NACO Technologies)	S-II[S-393]489
S-3010	Side Frame, Standard Pedestal-Type with Side Frame Key—Limiting Dimensions	S-II[S-3010]491
S-3011	Side Frame, Standard Pedestal-Type Size 6 in. × 11 in. with Side Frame Key—Limiting Dimensions	S-II[S-3011]493
S-3012	Side Frame, Alternate Standard Pedestal-Type with Side Frame Key—Application of Roller Bearing Unit	S-II[S-3012]495

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

**TABLE OF CONTENTS ARRANGED BY
DRAWING NUMBER**

(Drawings located in S-392)

Drawing No.	Description	Page
3608-F	Side Frame Opening Conditions Barber Stabilized Truck Type S-2-A 6 1/2-in. × 12-in. Journals 10-in. to Rail 8 1/2-in. Column Width	S-II[S-392]217
3655-F	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 5 1/2-in. × 10-in. Journals	S-II[S-392]218
3656-J	Side Frame Opening Conditions Barber Stabilized Truck Type S-2-A 6-in. × 11-in. Journals	S-II[S-392]219
3657-L	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-B, C 6-in. × 11-in. Journals	S-II[S-392]220
3658-K	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 6 1/2-in. × 12-in. Journals 6 1/2-in. Column Width	S-II[S-392]221
3703-M	Bolster End Conditions Barber Stabilized Truck Type S-2-A 6 1/2-in. × 12-in. Bearings 8 1/2-in. Column Width	S-II[S-392]222
3748-K	Bolster End Conditions Barber Stabilized Truck Type S-2-A 5 1/2-in. × 10-in. Journals 6-in. Column Width	S-II[S-392]223
3749-H	Bolster End Conditions Barber Stabilized Truck Type S-2-B 5 1/2-in. × 10-in. Journals 6-in. Column Width	S-II[S-392]224
3750-J	Bolster End Conditions Barber Stabilized Truck Type S-2-C 5 1/2-in. × 10-in. Journals 6-in. Column Width	S-II[S-392]225
3751-N	Bolster End Conditions Barber Stabilized Truck Type S-2-A 6-in. × 11-in. Journals 6 1/2-in. Column Width	S-II[S-392]226
3752-S	Bolster End Conditions Barber Stabilized Truck Type S-2-B 6-in. × 11-in. Journals 6 1/2-in. Column Width	S-II[S-392]227

IMPLEMENTED 02/15/2019

AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes

Drawing No.	Description	Page
3753-V	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Journals 6 1/2-in. Column Width	S-II[S-392]228
3754-N	Bolster End Conditions Barber Stabilized Truck Type S-2-A 6 1/2-in. × 12-in. Journals 6 1/2-in. Column Width	S-II[S-392]229
3755-R	Bolster End Conditions Barber Stabilized Truck Type S-2-B 6 1/2-in. × 12-in. Journals 6 1/2-in. Column Width	S-II[S-392]230
3756-U	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 6 1/2-in. Column Width	S-II[S-392]231
3821-K	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 7-in. × 12-in. Journals	S-II[S-392]232
3887-J	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 6 1/2-in. × 12-in. Journals 9 3/8-in. to Rail 8 1/2-in. Column Width	S-II[S-392]233
3888-Q	Bolster End Conditions Barber Stabilized Truck Type S-2-B 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]234
3897-W	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]235
3906-J	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 6 1/2-in. × 12-in. Journals Low Profile 8 1/2-in. Column Width	S-II[S-392]236
3907-T	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]237
3924-M	Bolster End Conditions Barber Stabilized Truck Type S-2-A 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]238
3993-E	Side Frame Opening Conditions Barber Stabilized Truck Type S-2-A 6 1/2-in. × 12-in. Bearings 10 in. to Rail Canadian Wide Land	S-II[S-392]239

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

IMPLEMENTED 02/15/2019

Drawing No.	Description	Page
4048-E	Bolster End Conditions Barber Stabilized Truck Types S-2-A 7-in. × 12-in. Bearings	S-II[S-392]240
4110-E	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 5 1/2-in. × 10-in. Journals 9 3/8 in. to Rail 7 1/2-in. Column Width	S-II[S-392]241
4111-E	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A 6-in. × 11-in. Journals 9 3/8 in. to Rail 8-in. Column Width	S-II[S-392]242
4112-F	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-B, C 6-in. × 11-in. Journals 9 3/8 in. to Rail 8-in. Column Width	S-II[S-392]243
4113-E	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 6 1/2-in. × 12-in. Journals 9 3/8 in. to Rail 8-in. Column Width	S-II[S-392]244
4115-G	Bolster End Conditions Barber Stabilized Truck Type S-2-A 5 1/2-in. × 10-in. Journals 7 1/2-in. Column Width	S-II[S-392]245
4116-H	Bolster End Conditions Barber Stabilized Truck Type S-2-B 5 1/2-in. × 10-in. Journals 7 1/2-in. Column Width	S-II[S-392]246
4117-G	Bolster End Conditions Barber Stabilized Truck Type S-2-C 5 1/2-in. × 10-in. Journals 7 1/2-in. Column Width	S-II[S-392]247
4118-K	Bolster End Conditions Barber Stabilized Truck Type S-2-A 6-in. × 11-in. Journals 8-in. Column Width	S-II[S-392]248
4119-M	Bolster End Conditions Barber Stabilized Truck Type S-2-B 6-in. × 11-in. Journals 8-in. Column Width	S-II[S-392]249
4120-P	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Journals 8-in. Column Width	S-II[S-392]250
4121-L	Bolster End Conditions Barber Stabilized Truck Type S-2-A 6 1/2-in. × 12-in. Journals 8-in. Column Width	S-II[S-392]251

AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes

Drawing No.	Description	Page
4122-K	Bolster End Conditions Barber Stabilized Truck Type S-2-B 6 1/2-in. × 12-in. Journals 8-in. Column Width	S-II[S-392]252
4123-N	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8-in. Column Width	S-II[S-392]253
4156-L	Bolster End Conditions Barber Stabilized Truck Type S-2-A 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]254
4188-B	Bolster End Conditions Barber Stabilized Truck Type S-2-C 7-in. × 12-in. Journals	S-II[S-392]255
4234-A	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 7-in.-Diameter Axle 16-Axle Depressed Center Flatcar	S-II[S-392]256
4428-P	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]257
4431-L	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8-in. Column Width	S-II[S-392]258
4433-Q	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 6 1/2-in. Column Width	S-II[S-392]259
4507-S	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Bearings 6 1/2-in. Column Width	S-II[S-392]260
4523-E	Side Frame Opening Conditions Barber Stabilized Truck Types S-2-A, B, C 6 1/2-in. × 12-in. Journals 9 3/8 in. to Rail Canadian Wide Land	S-II[S-392]261
4733-Q	Bolster End Conditions with Wear Plates Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Bearings	S-II[S-392]262
4774-H	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]263

IMPLEMENTED 02/15/2019

AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes

IMPLEMENTED 02/15/2019

Drawing No.	Description	Page
4783-A	Bolster End Conditions Barber Stabilized Truck Type S-2-A 7-in. × 12-in. Journals	S-II[S-392]264
4832-B	Side Frame Opening Conditions Barber Stabilized Truck Type S-2-HD 7-in. × 12-in. Journals	S-II[S-392]265
4833-D	Bolster End Conditions with Wear Plates Barber Stabilized Truck Type S-2-HD 7-in. × 12-in. Journals	S-II[S-392]266
4841-AC	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Bearings Dual-Rate Springs	S-II[S-392]267
4852-L	Side Frame Opening Conditions Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Journals Low-Profile Design	S-II[S-392]268
4867-L	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]269
4885-M	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 6 1/2-in. Column Width	S-II[S-392]270
4984-H	Side Frame Opening Conditions Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Journals	S-II[S-392]271
4989-L	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8 1/2-in. Column Width	S-II[S-392]272
5056-B	Side Frame Opening Conditions Barber Stabilized Truck 6 1/2-in. × 12-in. Journals Mark II Dual-Rate Load Springs 6 1/2-in. Column Width	S-II[S-392]273
5074-G	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Bearings 8-in. Column Width	S-II[S-392]274
51365-M	ASF-K Ride Control or Barber Stabilized Trucks Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]125
51391-K	ASF-K Ride Control Truck with Increased Column Clearance Standard Bolster End Construction 6-in. × 11-in. Journals	S-II[S-392]126

AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes

Drawing No.	Description	Page
51396-M	ASF-K Ride Control Truck Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]127
5140-F	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 6 1/2-in. Column Width	S-II[S-392]275
5141-H	Bolster End Conditions Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8-in. Column Width	S-II[S-392]276
51413-P	ASF-K Ride Control Truck with Increased Column Clearance Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]128
51414-M	ASF-K Ride Control Truck with Increased Column Clearance Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]129
51416-N	ASF-K Ride Control Truck with Increased Column Clearance and Snubber Retainers Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]130
51417-N	ASF-K Ride Control Truck with Increased Column Clearance and Snubber Retainers Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]131
51511-F	ASF-K Ride Control or Barber Stabilized Trucks Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]132
51596-C	ASF-K Ride Control Truck with Increased Column Clearance Standard Bolster End Construction 6-in. × 11-in. Journals	S-II[S-392]133
51597-D	ASF-K Ride Control Truck Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]134
51598-F	ASF-K Ride Control Truck with Increased Column Clearance Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]135
5161-F	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals 8-in. Column Width	S-II[S-392]277
51613-D	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]136
51647-E	ASF-K Ride Control Truck with Increased Column Clearance Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]137

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

IMPLEMENTED 02/15/2019

Drawing No.	Description	Page
51676-C	ASF-K Super Service Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]138
51677-C	ASF-K Super Service Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]139
51678-E	ASF-K Super Service Ride Control Truck Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]140
51780-B	ASF-K Ridemaster Truck Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]141
51781-C	ASF-K Ridemaster Truck Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]142
51788-B	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 7-in. × 12-in. Journals	S-II[S-392]143
51789-B	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 7-in. × 12-in. Journals	S-II[S-392]144
51790-B	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 7-in. × 12-in. Journals	S-II[S-392]145
51791-B	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6-in. × 11-in. Journals	S-II[S-392]146
51792-B	ASF-K Ridemaster Truck Standard Side Frame Column and Spring Seat Construction 6-in. × 11-in. Journals	S-II[S-392]147
51793-C	ASF-K Ride Control Truck Low Level Bolster End Construction 6-in. × 11-in. Journals	S-II[S-392]148
51794-B	ASF-K Ride Control Truck Standard Bolster End Construction 7-in. × 12-in. Journals	S-II[S-392]149
51795-B	ASF-K Ridemaster Truck Standard Bolster End Construction 6-in. × 11-in. Journals	S-II[S-392]150
51796-B	ASF-K Ride Control Truck Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]151
51800-C	ASF-K Ride Control Truck Low Level Bolster End Construction 6-in. × 11-in. Journals	S-II[S-392]152

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

Drawing No.	Description	Page
51801-C	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6-in. × 11-in. Journals	S-II[S-392]153
51804-B	ASF-K Truck Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]154
51805-B	ASF-K Ridemaster Truck Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]155
51810-B	ASF-K Ride Control Truck Standard Bolster End Construction 7-in. × 12-in. Journals	S-II[S-392]156
51817-D	ASF-K Super Service Ridemaster Truck Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]157
51818-B	ASF-K Super Service Ridemaster Truck Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]158
5241-G	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-A 6 1/2-in. × 12-in. Journals 8-in. Column Width	S-II[S-392]278
5262-C	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-B 5 1/2-in. × 10-in. Journals 6-in. Column Width	S-II[S-392]279
5283-E	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-A 6-in. × 11-in. Journals 6 1/2-in. Column Width—for Canada	S-II[S-392]280
5404-G	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Journals 6 1/2-in. Column Width	S-II[S-392]281
5457-B	Side Frame Opening Conditions Barber Stabilized Truck Type S-2-HD 7-in. × 12-in. Bearings	S-II[S-392]282
5458-B	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-HD 7-in. × 12-in. Bearings	S-II[S-392]283
54601-K	ASF-K Ride Control Truck Standard Bolster End Construction 5-in. × 9-in. and 5 1/2-in. × 10-in. Journals	S-II[S-392]160
54602-P	ASF-K Ride Control Truck Standard Bolster End Construction 6-in. × 11-in. Journals	S-II[S-392]161

IMPLEMENTED 02/15/2019

AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes

IMPLEMENTED 02/15/2019

Drawing No.	Description	Page
54603-M	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 5-in. × 9-in. and 5 1/2-in. × 10-in. Journals	S-II[S-392]162
54604-P	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6-in. × 11-in. Journals	S-II[S-392]163
54660-N	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]164
54661-N	ASF-K Ride Control Truck Standard Bolster End Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]165
54715-M	ASF-K Ride Control or Barber Stabilized Trucks Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]166
54728-L	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6-in. × 11-in. Journals	S-II[S-392]167
54906-M	ASF-K Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6 1/2-in. × 12-in. Journals	S-II[S-392]168
5535-H	Bolster End Conditions Barber Stabilized Truck Type S-2-D 6 1/2-in. × 12-in. Bearings D5 and D7 Springs	S-II[S-392]284
5536-B	Side Frame Opening Conditions Barber Stabilized Truck S-2-D 6 1/2-in. × 12-in. Journals D5 and D7 Springs	S-II[S-392]285
5667-J	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-HD 6-in. × 11-in. Journals D5 Springs	S-II[S-392]286
5738-B	Side Frame Opening Conditions Barber Stabilized Truck S-2-D 6 1/2-in. × 12-in. Journals D7 Springs 4 1/4-in. Spring Travel	S-II[S-392]287
5750-C	Bolster End Conditions Barber Stabilized Truck Type S-2-D 6 1/2-in. × 12-in. Bearings D5 and D7 Springs	S-II[S-392]288
5753-A	Side Frame Opening Conditions Barber Stabilized Truck S-2-HD 6-in. × 11-in. Bearings D5 Springs 3 11/16-in. Spring Travel	S-II[S-392]289

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

Drawing No.	Description	Page
5779-B	Bolster End Conditions Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Journals D5 Springs As-Cast Square Pocket	S-II[S-392]290
5798-F	Side Frame Conditions Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 and D7 Springs	S-II[S-392]291
5799-G	Bolster End Conditions with Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D-5 and D7 Springs	S-II[S-392]292
5801-C	Bolster End Conditions Barber Stabilized Truck Type S-2-D 6 1/2-in. × 12-in. Bearings D-5 and D7 Springs	S-II[S-392]293
5808-B	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Bearings 6 1/2-in. Column Width	S-II[S-392]294
58119-D	ASF-K Super Service Ride Control Truck Standard Bolster End Construction 6-in. × 11-in. Journals	S-II[S-392]169
58120-C	ASF-K Super Service Ride Control Truck Standard Side Frame Column and Spring Seat Construction 6-in. × 11-in. Journals	S-II[S-392]170
5816-B	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Bearings 6 1/2-in. Column Width	S-II[S-392]295
5830-E	Bolster End Conditions Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D-5 and D7 Springs As-Cast Square Pocket	S-II[S-392]296
5835	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-HD 7-in. × 12-in. Bearings Dual-rate Springs	S-II[S-392]297
5855-D	Bolster End Conditions Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Journals D5 Springs Square Pocket with Wear Plates	S-II[S-392]298
5898-F	Bolster End Conditions Barber Stabilized Truck Type S-2-D 6 1/2-in. × 12-in. Journals D5 and D7 Springs 263 and 286 K Grl Spring Group	S-II[S-392]299

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

IMPLEMENTED 02/15/2019

Drawing No.	Description	Page
5939-F	Bolster End Conditions Barber Stabilized Truck Type S-2-E 6 1/2-in. × 12-in. Journals	S-II[S-392]300
5940-E	Side Frame Conditions Barber Stabilized Truck Type S-2-E 6 1/2-in. × 12-in. Journals D3, D5, and D7 Springs	S-II[S-392]301
5947-A	Bolster End Conditions with Pocket and Side Wall Wear Plates Barber Stabilized Truck Type S-2-HD 7-in. × 12-in. Journals	S-II[S-392]302
5952-A	Bolster End Conditions with Square Pocket and Wear Plates Barber Stabilized Truck Type S-2-HD 7-in. × 12-in. Journals	S-II[S-392]303
5954-A	Bolster End Conditions with Pocket and Side Wall Wear Plates Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Journals	S-II[S-392]304
5969	Bolster End Conditions with Pocket and Side Wall Wear Plates Barber Stabilized Truck Type S-2-C 6 1/2-in. × 12-in. Journals	S-II[S-392]305
5977-B	Bolster End Conditions with Pocket and Side Wall Wear Plates Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Journals	S-II[S-392]306
6007-C	Bolster End Conditions with Square Pocket and Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 and D7 Spring	S-II[S-392]307
6057-C	Bolster End Conditions with Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals Dual Rate Springs	S-II[S-392]308
6072-B	Bolster End Conditions Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs As Cast	S-II[S-392]309
6081-A	Side Frame Conditions Barber Stabilized Truck Type S-2-E 6-in. × 11-in. Journals D5 Springs	S-II[S-392]310
6082-A	Bolster End Conditions Barber Stabilized Truck Type S-2-E 6-in. × 11-in. Journals	S-II[S-392]311
6083	Side Frame Conditions Barber Stabilized Truck Type S-2-E 6-in. × 11-in. Journals D5 Springs Low Conveyance	S-II[S-392]312

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

Drawing No.	Description	Page
6084-C	Bolster End Conditions Barber Stabilized Truck Type S-2-E 6-in. × 11-in. Journals Low Conveyance	S-II[S-392]313
6104-A	Bolster End Conditions Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D-5 263 and 286 K Grl Spring Group	S-II[S-392]314
6143-C	Bolster End Conditions Barber Stabilized Truck Type S-2-E 6 1/2-in. × 12-in. Journals	S-II[S-392]315
6144-C	Side Frame Conditions Barber Stabilized Truck Type S-2-E 6 1/2-in. × 12-in. Journals D5 and D7 Springs	S-II[S-392]316
6147-C	Bolster End Conditions with Square Pockets and Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. D5 Springs	S-II[S-392]317
6148-C	Side Frame Conditions Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs	S-II[S-392]318
6149-C	Side Frame Conditions Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs	S-II[S-392]319
6150-B	Bolster End Conditions with Square Pockets and Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs	S-II[S-392]320
6183-A	Bolster End Conditions with Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs	S-II[S-392]321
6189-A	Bolster End Conditions with Pockets and Side Wall Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs	S-II[S-392]322
6201-A	Bolster End Conditions Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs Integral Cast Insert	S-II[S-392]323

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

IMPLEMENTED 02/15/2019

Drawing No.	Description	Page
6218-A	Bolster End Conditions with Pockets and Side Wall Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 and D7 Springs	S-II[S-392]324
6219-B	Bolster End Conditions Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs As Cast with Tapered Wall	S-II[S-392]325
6222	Bolster End Conditions Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Journals D5 Springs As Cast	S-II[S-392]326
6300	Side Frame Conditions Barber Stabilized Truck Type S-2-HD-9C 7-in. × 12-in. Journals D5 Springs	S-II[S-392]327
6301	Bolster End Conditions with Wear Plates Barber Stabilized Truck Type S-2-HD-9C 7-in. × 12-in. Journals D5 Springs	S-II[S-392]328
6308	Bolster End Conditions with Pocket Wear Plates Barber Stabilized Truck Type S-2-C 6-in. × 11-in. Journals	S-II[S-392]329
6310	Bolster End Conditions with Pockets and Side Wall Wear Plates Barber Stabilized Truck Type S-2-HD-9C 6 1/2-in. × 12-in. Journals D5 Springs	S-II[S-392]330
6333	Bolster End Conditions with Pockets and Side Wall Wear Plates Barber Stabilized Truck Type S-2-HD 6-in. × 11-in. Journals D5 Springs	S-II[S-392]331
6420	Bolster End Conditions with Square Pocket and Wear Plates Barber Stabilized Truck Type S-2-HD 6 1/2-in. × 12-in. Journals Dual Rate Springs	S-II[S-392]332
B-10393-C	Standard Bolster End Construction for Buckeye 6 1/2 in. × 12 in. Journal Cushion-Ride Truck	S-II[S-392]189
B-10511-B	Standard Bolster End Construction for Buckeye 6 in. × 11 in. Journal Cushion-Ride Truck	S-II[S-392]190
B-10512-B	Standard Bolster End Construction for Buckeye 6 1/2 in. × 12 in. Journal Cushion-Ride Truck	S-II[S-392]191
B-10546-B	Standard Bolster End Construction for Buckeye 6 1/2 in. × 12 in. Journal Cushion-Ride Truck	S-II[S-392]192

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

Drawing No.	Description	Page
B-13601	Standard Side Frame Column and Spring Seat Construction for Buckeye 6 1/2 in. × 12 in. Journal XC-R Truck	S-II[S-392]193
B-13602	Standard Side Frame Column and Spring Seat Construction for Buckeye 6 in. × 11 in. Journal XC-R Truck	S-II[S-392]194
B-13603	Standard Side Frame Column and Spring Seat Construction for Buckeye 6 in. × 11 in. Journal XC-R Truck	S-II[S-392]195
B-13604	Side Frame Column and Spring Seat Construction for Buckeye 6 in. × 11 in. Journal Low Conveyance XC-R Truck	S-II[S-392]196
B-13605-A	Standard Bolster End Construction for Buckeye 6 1/2 in. × 12 in. Journal XC-R Truck	S-II[S-392]197
B-13606-A	Standard Bolster End Construction for Buckeye 6 in. × 11 in. Journal XC-R Truck	S-II[S-392]198
B-13607-B	Standard Bolster End Construction for Buckeye 6 in. × 11 in. Journal XC-R Truck	S-II[S-392]199
B-13608-A	Bolster End Construction for Buckeye 6 in. × 11 in. Journal Low Conveyance XC-R Truck	S-II[S-392]200
B-13609-A	Standard Bolster End Construction for Buckeye 7 in. × 12 in. Journal XC-R Truck	S-II[S-392]201
B-13610	Standard Side Frame Column and Spring Seat Construction for Buckeye 7 in. × 12 in. Journal XC-R Truck	S-II[S-392]202
B-13980	Standard Side Frame Column and Spring Seat Construction for Buckeye 7 in. × 12 in. Journal XC-R Truck	S-II[S-392]203
B-14415	Bolster End Construction for Buckeye 6 1/2 in. × 12 in. Journal XC-R Truck (for Special Column GIB Spacing)	S-II[S-392]204
B-14434	Side Frame Column and Spring Seat Construction for Buckeye 6 1/2 in. × 12 in. Journal XC-R Truck	S-II[S-392]205
B-14735	Standard Bolster End Construction for Buckeye 6 in. × 11 in. Journal XC-R Truck	S-II[S-392]206
B-9502-D	Standard Side Frame Column and Spring Seat Construction for Buckeye 5 1/2 in. × 10 in. Journal Cushion-Ride Truck	S-II[S-392]183

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

IMPLEMENTED 02/15/2019

Drawing No.	Description	Page
B-9503-C	Standard Bolster End Construction for Buckeye 5 1/2 in. × 10 in. Journal Cushion-Ride Truck	S-II[S-392]184
B-9504-D	Standard Side Frame Column and Spring Seat Construction for Buckeye 6 in. × 11 in. Journal Cushion-Ride Truck	S-II[S-392]185
B-9505-C	Standard Bolster End Construction for Buckeye 6 in. × 11 in. Journal Cushion-Ride Truck	S-II[S-392]186
B-9506-D	Standard Side Frame Column and Spring Seat Construction for Buckeye 6 1/2 in. × 12 in. Journal Cushion-Ride Truck	S-II[S-392]187
B-9507-D	Standard Bolster End Construction for Buckeye 6 1/2 in. × 12 in. Journal Cushion-Ride Truck	S-II[S-392]188
N41806	ASF C-1 Truck Center Portion of 5 × 9 and 5 1/2 × 10 Side Frame 2 1/2 in., 3 1/16 in., and 3 11/16 in. Spring Deflection	S-II[S-392]65
N41807	ASF C-1 Truck 5 × 9 and 5 1/2 × 10 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]66
N41808	ASF C-1 Truck 5 × 9 and 5 1/2 × 10 Bolster End 3 1/16 in. Spring Deflection	S-II[S-392]67
N41809	ASF C-1 Truck 5 × 9 and 5 1/2 × 10 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]68
N41810	ASF C-1 Truck Center Portion of 6 × 11 Side Frame 2 1/2 in., 3 1/16 in., and 3 11/16 in. Spring Deflection	S-II[S-392]69
N41811	ASF C-1 Truck 6 × 11 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]70
N41812	ASF C-1 Truck 6 × 11 Bolster End 3 1/16 in. Spring Deflection	S-II[S-392]71
N41813	ASF C-1 Truck 6 × 11 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]72
N41814	ASF C-1 Truck Center Portion of 6 1/2 × 12 Side Frame 2 1/2 in., 3 1/16 in., and 3 11/16 in. Spring Deflection	S-II[S-392]73
N41815	ASF C-1 Truck 6 1/2 × 12 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]74

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

Drawing No.	Description	Page
N44219	ASF C-1 Truck 6 1/2 × 12 Bolster End 3 1/16 in. Spring Deflection	S-II[S-392]75
N44220	ASF C-1 Truck 6 1/2 × 12 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]76
N47573	ASF C-1 Truck 6 × 11 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]77
N47574	ASF C-1 Truck 6 × 11 Bolster End 3 1/16 in. Spring Deflection	S-II[S-392]78
N47575	ASF C-1 Truck 6 × 11 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]79
N47576	ASF C-1 Truck 6 1/2 × 12 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]80
N47577	ASF C-1 Truck 6 1/2 × 12 Bolster End 3 1/16 in. Spring Deflection	S-II[S-392]81
N47578	ASF C-1 Truck 6 1/2 × 12 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]82
N48171	ASF Super C-1 Wedgelock Truck 8-Coil Bolster End 6 1/2 in. × 12 in. Journals	S-II[S-392]83
N48172	ASF Super C-1 Wedgelock Truck 8-Coil Bolster End 6 1/2 in. × 12 in. Journals	S-II[S-392]84
N48173	ASF Super C-1 Wedgelock Truck 8-Coil Bolster End 6 1/2 in. × 12 in. Journals	S-II[S-392]85
N48174	ASF Super C-1 Truck 6 × 11 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]86
N48175	ASF Super C-1 Truck 6 × 11 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]87
N48176	ASF Super C-1 Truck 6 × 11 Bolster End 3 1/16 in. Spring Deflection	S-II[S-392]88
N48177	ASF Super C-1 Wedgelock Truck 6 × 11 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]89

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

IMPLEMENTED 02/15/2019

Drawing No.	Description	Page
N48178	ASF Super C-1 Wedgelock Truck 6 × 11 Bolster End 3 1/16 in. Spring Deflection	S-II[S-392]90
N48179	ASF Super C-1 Wedgelock Truck 6 × 11 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]91
N48180	ASF Super C-1 Truck 6 1/2 × 12 Bolster End 3 1/16 in. Spring Deflection	S-II[S-392]92
N48181	ASF Super C-1 Truck 6 1/2 × 12 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]93
N48182	ASF Super C-1 Truck 6 1/2 × 12 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]94
N48185	ASF Super C-1 Wedgelock Truck Center Portion of 8-Coil Side Frame 6 1/2 in. × 12 in. Journals	S-II[S-392]95
N48186	ASF Super C-1 Truck Center Portion of 6 1/2 × 12 Side Frame 2 1/2 in., 3 1/16 in., and 3 11/16 in. Spring Deflection	S-II[S-392]96
N48187	ASF Super C-1 Wedgelock Truck Center Portion of 6 × 11 Side Frame 2 1/2 in., 3 1/16 in., and 3 11/16 in. Spring Deflection	S-II[S-392]97
N48188	ASF Super C-1 Truck Center Portion of 6 × 11 Side Frame 2 1/2 in., 3 1/16 in., and 3 11/16 in. Spring Deflection	S-II[S-392]98
N51191	ASF Super C-1 Wedgelock Truck Center Portion of 9-Coil 6 1/2 × 12 Side Frame 3 11/16 in. and 4 1/4 in. Spring Deflection	S-II[S-392]99
N51192	ASF Super C-1 Wedgelock Truck 9-Coil 6 1/2 × 12 Bolster End 3 11/16 in. and 4 1/4 in. Spring Deflection	S-II[S-392]100
N51372	ASF Swing Motion Truck Bolster End 6 in. × 11 in. Journals	S-II[S-392]101
N51373	ASF Swing Motion Truck Bolster End 6 1/2 in. × 12 in. Journals	S-II[S-392]102
N51374	ASF Swing Motion Truck Center Portion of 6 × 11 Side Frame 3 11/16 in. and 4 1/4 in. Spring Deflection	S-II[S-392]103
N51375	ASF Swing Motion Truck Center Portion of 6 1/2 × 12 Side Frame 3 11/16 in. and 4 1/4 in. Spring Deflection	S-II[S-392]104

AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes

Drawing No.	Description	Page
N52006	ASF Super C-1 Truck Center Portion of Side Frame 7 in. × 12 in. Journals	S-II[S-392]105
N52007	ASF Super C-1 Wedgelock Truck Center Portion of 8-Coil Side Frame 7 in. × 12 in. Journals	S-II[S-392]106
N52008	ASF Super C-1 Wedgelock Truck Center Portion of Low Deck Side Frame 6 in. × 11 in. Journals	S-II[S-392]107
N52009	ASF Swing Motion Truck Center Portion of Side Frame 7 in. × 12 in. Journals	S-II[S-392]108
N52010	ASF Swing Motion Truck Center Portion of Low Deck Side Frame 6 in. × 11 in. Journals	S-II[S-392]109
N52011	ASF Swing Motion Truck Center Portion of Low Deck Side Frame 6 in. × 11 in. Journals	S-II[S-392]110
N52012	ASF Super C-1 Truck 7 × 12 Bolster End 2 1/2 in. Spring Deflection	S-II[S-392]111
N52013	ASF Super C-1 Truck 7 × 12 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]112
N52014	ASF Super C-1 Wedgelock Truck 8-Coil Bolster End 7 in. × 12 in. Journals	S-II[S-392]113
N52015	ASF Super C-1 Wedgelock Truck 8-Coil 7 × 12 Bolster End 3 11/16 in. Spring Deflection	S-II[S-392]114
N52016	ASF Super C-1 Wedgelock Truck Low Deck Bolster End 6 in. × 11 in. Journals	S-II[S-392]115
N52017	ASF Super C-1 Wedgelock Truck 9-Coil 7 × 12 Bolster End 3 11/16 in. and 4 1/4 in. Spring Deflection	S-II[S-392]116
N52018	ASF Swing Motion Truck Bolster End 7 in. × 12 in. Journals	S-II[S-392]117
N52019	ASF Swing Motion Truck Low Deck Bolster End 6 in. × 11 in. Journals	S-II[S-392]118
N52020	ASF Super C-1 Wedgelock Truck Center Portion of 9-Coil 7 × 12 Side Frame 3 11/16 in. and 4 1/4 in. Spring Deflection	S-II[S-392]119

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

Drawing No.	Description	Page
N53164	ASF Swing Motion Truck Center Portion of Low Deck Side Frame 6 in. × 11 in. Journals	S-II[S-392]120
PN1657-A	ASF—Keystone Split Wedge Bolster End Condition Type S-2-B&C 6 1/2 × 12 Journals Various Column Widths	S-II[S-392]172
PN1658-A	ASF—Keystone Split Wedge Bolster End Condition Type S-2-B&C 6 1/2 × 11 Journals Various Column Widths	S-II[S-392]173
PN1659-A	ASF—Keystone Split Wedge Bolster End Condition Type S-2-B&C 5 1/2 × 10 Journals Various Column Widths	S-II[S-392]174
PN1660-A	ASF—Keystone Split Wedge Bolster End Condition Type S-2-A 6 1/2 × 12 Journals Various Column Widths	S-II[S-392]175
PN1661-A	ASF—Keystone Split Wedge Bolster End Condition Type S-2-A 6 1/2 × 11 Journals Various Column Widths	S-II[S-392]176
PN1690-A	HC ASF—Keystone Split Wedge Bolster End Condition 6 1/2 × 12 Journals	S-II[S-392]177
PN1691-A	HC ASF—Keystone Split Wedge Bolster End Condition 7 × 12 Journals	S-II[S-392]178
PN1692-A	HC ASF—Keystone Split Wedge Bolster End Condition 6 1/2 × 11 Journals	S-II[S-392]179
PN1693-A	HC ASF—Keystone Split Wedge Bolster End Condition 6 1/2 × 12 Journals	S-II[S-392]180

IMPLEMENTED 02/15/2019

**AAR Manual of Standards and Recommended Practices
Truck Details and Casting Codes**

THIS PAGE LEFT BLANK INTENTIONALLY

IMPLEMENTED 02/15/2019